

KOMAD 303 FUEL ADDITIVE

dispersant



Polysisobutenyl-mono-succinimide type ashless dispersant additive in mineral oil raffinate solvent.

Application

Applicable for formulation of engine cleaning fluids, cleaning oils used in metal cleaning and heating systems.

Applicable as fuel system cleaning additive (e.g. detergent in diesel fuel).

Features and benefits

Halogen-free

Burns without forming toxic halogen-substances.
Non-corrosive.

Ashless

Burns without forming ash and deposits.
Ensures longer lifetime for flue gas treatment systems.

Excellent dispersant properties

Prohibits aggregation and segregation of contaminants, formation of deposits.

Properties

Properties	Typical values
Appearance	clear, bright, viscous liquid
Density at 15°C [g/cm ³]	0.92
Kinematic viscosity at 100 °C [mm ² /s]	220
Flash point (Cleveland) [°C]	250
Base number (BN) [mg KOH/g]	86
Nitrogen content (Kjeldahl) [mass %]	3.25

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Recommended blending and pumping temperature is 60-80 °C.

In the original container under the recommended storage conditions: 24 months

Recommended storage temperature: -10°C - +80°C

KOMAD 303 FUEL ADDITIVE

dispersant



Ordering information

Custom Tariff Number 38119000

SAP code and packaging:

13301000 KOMAD 303 FUEL ADDITIVE O 180KG

216.5 l steel drum (for order only)

Order booking:

Please contact your local distributor or sales partner for ordering details.