

# KOMAD 313

## anti-fouling additive



### Application

Suitable for formulation of anti-fouling additives in petrochemical and refinery systems.

### Features and benefits

Ashless

Burns without forming ash and deposits.  
Ensures longer lifetime for flue gas treatment systems.

Halogen-free

Burns without forming toxic halogen-substances.  
Non-corrosive.

Outstanding cleaning effect

Dissolves deposits from the inner walls of the system and prevents further deposition

### Properties

Properties	Typical values
Appearance	brown, viscous liquid
Density at 15°C [g/cm <sup>3</sup> ]	0.88
Kinematic viscosity at 50 °C [mm <sup>2</sup> /s]	450
Base number (BN) [mg KOH/g]	33
Iron content (ICP) [mg/kg]	max. 5
Active ingredient content [mass %]	min. 30
Chlorine content [mass %]	max. 0.1

The characteristics in table are typical values of the product and do not constitute a specification.

### Storage and handling instructions

Store in the original container in dry, properly ventilated area. Keep away from direct flame and other sources of ignition. Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Recommended blending and pumping temperature is 60-80 °C.

In the original container under the recommended storage conditions: 24 months

Recommended storage temperature: -30°C - +80°C

### Ordering information

Custom Tariff Number 38112100

#### SAP code and packaging:

13004076 KOMAD 313 170KG

216.5 l steel drum (for order only)

13004115 KOMAD 313 CC

Customer IBC (for order only)

#### Order booking:

Please contact your local distributor or sales partner for ordering details.